



PUSH THE BOUNDARIES

SIMPLE SOLUTION FOR
SOLID CONSTRUCTION



PLUMETT/ULTIMAZ™

CONNECTED TO ANY ELECTRICAL DRILL, THE ULTIMAZ™-P2P HANDLE MICRO-CABLES FTTx IN THE SIMPLEST WAY.



www.plumettaz.com

Plumettaz S.A. | Route de la Gribannaz 7 | 1880 Bex - Switzerland
T +41 24 463 06 06 | info@plumettaz.com

MAIN ACCESSORIES

Standard equipment:

1 box for the UltimaZ and its accessories / 1 set of tools / 1 bottle of lubricant Micro jetting lube / 1 operation and maintenance manual

Standard version	UltimaZ P2P	UltimaZ P2P	UltimaZ P2P
Type	V20	F5 / F7 / F15	Pusher
Cable dia. [mm]	0.8-4.0	0.8-1.4 / 1.4-1.8 / 1.6-2.8	max. 4.0 (**)
Duct OD [mm]	3.0-12.0	3.0-12.0	max. 12.0 (**)
Drive unit	Electrical drill	Electrical drill	Electrical drill
Pushing force [N]	0-20	5 / 7.5 / 15	-
Radial pressure on cable [N]	2-80	55	80
Max. speed [m/min]	150	150	150
Max. air pressure [bar]	12	12	12
Dimension of apparatus l x w x h [mm]	215 x 136 x 132	160x136 x144 (F5/F7) 166x136 x144 (F15)	160 x 136 x 144
Dimension of apparatus with case l x w x h [mm]	460 x 140 x 360	460 x 140 x 360	460 x 140 x 360
Weight of machine [kg]	1.700	1.200	1.100
Total weight [kg]	4.100	3.600	3.500

Specifications are subject to change without notice



Lubricator L4,
for the continuous lubrication of cables for a better Jetting performance



Micro Jetting Lube,
lubricant improving Jetting performance