



PUSH THE BOUNDARIES

SIMPLE SOLUTION FOR
SOLID CONSTRUCTION



PLUMETT INTELLI-MICROJET™

THE INTELLI-MICROJET™ MONITORS, SUPERVISES AND RECORDS THE PERFORMANCE OF THE INSTALLATION TO MAKE YOUR WORK MORE EFFICIENT. THANKS TO ITS EMBEDDED PLATFORM GENERATING A FULL REPORT ON THE INSTALLATION RESULTS.



www.plumettaz.com

Plumettaz S.A. | Route de la Gribannaz 7 | 1880 Bex - Switzerland
T +41 24 463 06 06 | info@plumettaz.com

MAIN ACCESSORIES

Standard equipment:

1 box for the Intelli-MicroJet and its accessories / 1 set of tools / 1 speed and distance indicator / 1 holder to fix the base plate of the IntelliBox / 1 air hose with quick release coupling Mody to connect to compressor / 1 driving wheel without steel tyre / 1 pressure wheel (aluminium) / 1 bottle of lubricant Micro Jetting Lube / 1 operation and maintenance manual

Standard version	Intelli-MicroJet	Intelli-MicroJet
Type	PRM-196	PR-196
Cable dia. [mm]	1.0-8.0	3.5-8.0
Duct OD [mm]	3.0-16	7.0-16
Drive unit	Pneumatic	Pneumatic
Max. air consumption of motor [m3/min]	0.2 (at 6 bar)	0.2 (at 6 bar)
Pushing force [N]	0-25 / 0-150	0-150
Radial pressure on cable [N]	15-180	15-180
Max. speed [m/min]	120	120
Max. air pressure [bar]	16	16
Intellibox, TFT display size ["]	7	7
Intellibox, battery life [h]	8	8
Intellibox, protection rating [IP]	65	65
Dimension of Intelli-MicroJet l x w x h [mm]	518 x 348 x 359	518 x 348 x 279
Dimension of Intellibox l x w x h [mm]	270 x 248 x 182	270 x 248 x 182
Dimension of Intelli-MicroJet with case l x w x h [mm]	620 x 420 x 410	620 x 420 x 410
Dimension of Intellibox with case l x w x h [mm]	620 x 420 x 280	620 x 420 x 280
Weight of Intelli-MicroJet and Intellibox [kg]	16.800	15.700
Total weight [kg]	41.900	40.800

Specifications are subject to change without notice



Lubricator L9,
for the continuous lubrication of cables for a better Jetting performance



Micro Jetting Lube,
lubricant improving Jetting performance



Figarino,
intermediate cable storage system, avoiding figure of 8