



www.plumettaz.com

Plumettaz S.A. | Route de la Gribannaz 7 | 1880 Bex - Switzerland
T +41 24 463 06 06 | info@plumettaz.com

© 2019 by Plumettaz SA, Bex - v1.0/01.03.2019



PLUMETT
PUSH THE BOUNDARIES
SIMPLE SOLUTION FOR
SOLID CONSTRUCTION

PLUMETT / MICROJET™

WHEN IT COMES TO FIBRE ACCURACY AND PRECISE TORQUE, THE MICROJET™
HANDLES MICRO-CABLES LIKE NO OTHER MACHINE.

MAIN ACCESSORIES

Standard equipment:

1 box for the MicroJet and its accessories / 1 set of tools / 1 speed and distance indicator /
 1 air hose with quick release coupling Mody to connect the compressor / 1 bottle of
 lubricant Micro jetting lube / 1 operation and maintenance manual

Standard version	MicroJet	MicroJet	Microjet
Type	PRM-196	PR-196	EM-25
Cable dia. [mm]	1.0-8.0	3.5-8.0	< 3.0
Duct OD [mm]	3.0-16	7.0-16	3.0-8.0
Drive unit	Pneumatic	Pneumatic	Electric
Clutch	Magnetic	-	Magnetic
Max. air consumption of motor [m ³ /min]	0.2 (at 6 bar)	0.2 (at 6 bar)	-
Pushing force [N]	0-25 / 0-150	0-150	0-25
Radial pressure on cable [N]	15-180	15-180	20-100
Max. speed [m/min]	120	120	50
Max. air pressure [bar]	16	16	16
Dimension of apparatus l x w x h [mm]	286 x 260 x 334	286 x 260 x 254	286 x 260 x 308
Dimension of apparatus with case l x w x h [mm]	620 x 420 x 340	620 x 420 x 340	620 x 420 x 340
Weight of machine [kg]	6.700	5.600	6.500
Total weight [kg]	17.100	16.000	18.600

Specifications are subject to change without notice



Lubricator L9,
for the continuous lubrication of cables for a
better Jetting performance



Micro Jetting Lube,
lubricant improving Jetting performance



Figarino,
intermediate cable storage system, avoiding
figure of 8