

MAIN ACCESSORIES



MP-50,
electronic digital recorder



Dynamometer



Connector (swivel) E-49-D,
up to 40 kN (4 tons)



VL 20,
speed and distance indicator



www.plumettaz.com

Plumettaz S.A. | Route de la Gribannaz 7 | 1880 Bex - Switzerland | T +41 24 463 06 06 | info@plumettaz.com

© 2020 by Plumettaz SA, Bex - v1.0/29.07.2020

PLUMETT
PUSH THE BOUNDARIES

SIMPLE SOLUTION FOR
SOLID CONNECTION



PLUMETT / CAPSTAN-WINCH 11/20 kN

A COMPACT AND LIGHT CAPSTAN WINCH SERIES
THAT COMBINED A **ROBUST PERFORMANCE**
AND YET AN EASY OPERATION.

www.plumettaz.com

Standard equipment :

1 set of tools / 1 engine / 1 operation and maintenance manual

Standard version	Capstan-winch	Capstan-winch	Capstan-winch	Capstan-winch
Type	TL 1118 D 900/6	TL 1118 DE 900/6	TL 2018 D 520/8	TL 2018 DE 520/8
Rope dia. [mm]	6-7	6-7	8-9	8-9
Max. rope length [m]	900 (Ø 6 mm)	900 (Ø 6 mm)	520 (Ø 8 mm)	520 (Ø 8 mm)
Drive unit	Mechanic	Electric	Mechanic	Electric
Type of engine	Honda Gasoline GX 160 SXE	Electric A2A 90 L4	Honda Gasoline GX 270 SXE	Electric A2A 100 LA4
Engine, max. power [kW]	3.6	1.5	6.3	3.0
Engine, max. RPM [min-1]	3600	1430	3600	1500
Current supply [V]	-	3x 400	-	3x 400
Max. line pull in 1st gear [daN]	1100	1100	2000	2000
Max. line pull in 2nd gear [daN]	550	550	1000	1000
Speed of pay-in rope in 1st gear [m/min]	7 - 16	0 - 13	5 - 11.9	0 - 9.5
Speed of pay-in rope in 2nd gear [m/min]	14 - 33	0 - 26	9.8 - 23.5	0 - 19
Speed of pay-out rope [m/min]	0 - 77	0 - 61	0 - 80	0 - 63
Length, handlebar in high position [mm]	1620	1730	1620	1730
Width [mm]	750	750	750	750
Height, wheels in high position [mm]	1230	1230	1230	1230
Weight of winch without rope [kg]	220	240	235	250

Specifications are subject to change without notice