

MAIN ACCESSORIES



MP-50,
electronic digital recorder
(included in version TL 3022 DRE)



Dynamometer
(included in version TL 3022 DRE)



Connector (swivel) E-49-D,
up to 40 kN (4 tons)



VL 20,
speed and distance indicator



www.plumettaz.com

Plumettaz S.A. | Route de la Gribannaz 7 | 1880 Bex - Switzerland | T +41 24 463 06 06 | info@plumettaz.com

© 2020 by Plumettaz SA, Bex - v2.0/16.12.2020

PLUMETT
PUSH THE BOUNDARIES

SIMPLE SOLUTION FOR
SOLID CONNECTION



PLUMETT / CAPSTAN-WINCH 24/30 kN

A COMPACT AND LIGHT CAPSTAN WINCH SERIES,
MOUNTED ON TRAILER, THAT COMBINED A **ROBUST**
PERFORMANCE AND YET AN EASY OPERATION.

www.plumettaz.com

Standard equipment :

1 set of tools / 1 engine / 1 eye coupling / 1 operation and maintenance manual



Standard version	Capstan-winch	Capstan-winch	Capstan-winch	Capstan-winch	Capstan-winch
Type	TL 2422 DRH 1300/8	TL 2422 DRHZ 1300/8	TL 3022 DRE 1050/9	TL 3022 DRH 1050/9	TL 3022 DRHZ 1050/9
Rope dia. [mm]	7-9	7-9	9	9	9
Max. rope length [m]	1300 (Ø 8 mm)	1300 (Ø 8 mm)	1050 (Ø 9 mm)	1050 (Ø 9 mm)	1050 (Ø 9 mm)
Drive unit	Hydraulic	Hydraulic	Electric	Hydraulic	Hydraulic
Type of engine	Honda Gasoline GX 630	Hatz Diesel Supra Silent Pack	Electric ME1507	Honda Gasoline GX 630	Hatz Diesel Supra Silent Pack
Engine, max. power [kW]	15.5	9.6	13	15.5	9.6
Engine, max. RPM [min-1]	3600	3000	8000	3600	3000
Current supply [V]			3x 48-120		
Hydraulic pressure [bar]	140	140		160	160
Max. line pull in 1st gear [daN]	2400	2400	3000	3000	3000
Max. line pull in 2nd gear [daN]	500	500	700	700	700
Speed of pay-in rope in 1st gear [m/min]	0 - 20	0 - 18	0 - 20	0 - 20	0 - 18
Speed of pay-in rope in 2nd gear [m/min]	0 - 80	0 - 68	0 - 80	0 - 80	0 - 68
Length, handlebar in high position [mm]	4054	4054	4054	4054	4054
Width [mm]	1702	1702	1702	1702	1702
Height, wheels in high position [mm]	1547	1547	1547	1547	1547
Weight of winch without rope [kg]	853	928	905	853	928

Specifications are subject to change without notice